

# EV2495



Inputs	USB Type-C®	✓
	● Network Connection	✓
	● Daisy Chain	✓
	● Power Delivery	✓
	● Connect Peripherals	✓
	DisplayPort	✓
	HDMI	✓
	DVI-D	
	D-Sub	
Eye Care Functions	✓	
Color / Frameless	<input type="checkbox"/> White <input checked="" type="checkbox"/> Black	
USB Ports	4	
Panel Size	24.1"	
Native Resolution	WUXGA 1920×1200	

NEW



EV2495



**EIZO®**



EV2495



EV2495-BK
-
EV2495-WT
EV2495-FBK
-
EV2495-FWT
IPS
LED
24.1" / 61.1 cm
1920 x 1200 (16:10 aspect ratio)
518.4 x 324 mm
0.270 x 0.270 mm / 94 ppi
16.77 million
178° / 178°
350 cd/m <sup>2</sup>
1000:1
5 ms (gray-to-gray)
USB Type-C (DisplayPort Alt Mode, HDCP 1.3), DisplayPort (HDCP 1.3), HDMI (HDCP 1.4)
USB Type-C (daisy chain)
USB Type-C: 31 - 76 kHz / 59 - 61 Hz
DisplayPort: 31 - 76 kHz / 59 - 61 Hz
HDMI: 15 - 76 kHz / 49 - 51 Hz, 59 - 61 Hz
-
-
USB 3.1 Gen 1: Type-B, USB 3.1 Gen 1: Type-C (DisplayPort Alt Mode, Power Delivery Source 70 W max.)
USB 3.1 Gen 1: Type-A x 3, USB 3.1 Gen 1: Type-C (DisplayPort Alt Mode, Power Delivery Source 15 W max.)
RJ-45 (1000BASE-T) Windows 10 / 8.1 (64-bit, 32-bit), macOS Sierra (10.12) or later
1.0 W + 1.0 W
Headphones (Stereo mini jack)
AC 100 - 240 V, 50 / 60 Hz
11 W
156 W
0.5 W or less
User1, User2, sRGB, Paper, Movie, DICOM
Yes

531 x 356.2 - 538.4 x 230 mm
531 x 344.2 x 53.7 mm
7.6 kg
4.9 kg
182.2 mm
35° Up, 5° Down
344°
90° (both clockwise and counter clockwise)
100 x 100 mm
TCO Certified Generation 8, EPEAT 2018 (US), TÜV/Ergonomics, TÜV/Low blue light content, TÜV/Flicker Free, TÜV/GS, RCM, CE, CB, cTUVus, FCC-B, CAN ICES-3 (B), TÜV/S, PSE, VCCI-B, EPA Energy Star, RoHS, WEEE, China RoHS, CCC, China Energy Label Grade1, EAC
Supported
USB Type-C (2 m)
AC power cord (2 m), VESA mounting screw x 4, setup guide
Five Years
Yes

