



## C-USBC/HM

USB Type-C (M) to HDMI (M) Cable

| HDMI | 4K/60 UHD (4:4:4)



C-USBC/HM is a high quality USB type-C (M) to HDMI (M) 6ft cable, that enables HDMI equipped monitors, TVs and projectors to be connected to any USB-C port that supports DP Alt Mode (DisplayPort Alternate Mode).

This cable support up to 4K@60Hz (4:4:4) resolution and delivers a direct connection that eliminates excess adapters and cabling, ensuring a tidy, professional installation

### FEATURES

Max. Resolution - 4K@60Hz (4:4:4)

HDCP 2.2 Support

Enables connecting an HDMI equipped monitor or projector to a USB-C port using a single cable

No special driver installation or additional power source is required

Regulatory Standards - CE, FCC and RoHS

Note - The cable's color can vary in some cases



## TECHNICAL SPECIFICATIONS

---

|                                              |                                                                                                        |
|----------------------------------------------|--------------------------------------------------------------------------------------------------------|
| Max. Resolution                              | 4K@60Hz (4:4:4)                                                                                        |
| Connector-A                                  | USB type-C (male), Nickel plated                                                                       |
| Connector-B                                  | HDMI Type-A (male), Nickel plated                                                                      |
| Length                                       | 6ft (1.8m)                                                                                             |
| Color                                        | White                                                                                                  |
| Environmental Conditions                     | Humidity: 30%–80%RH                                                                                    |
|                                              | Operating temperature: 0°C–50°C                                                                        |
|                                              | Storage Temperature: 10°C–70°C                                                                         |
| Regulatory Compliance (Standards Compliance) | Safety CE, FCC and RoHS                                                                                |
| Note                                         | USB type-C port must support DP Alt Mode (DisplayPort Alternate Mode) to be compatible with this cable |





#### CONFIGURATIONS

|              |                                  |
|--------------|----------------------------------|
| C-USBC/HM-6  | USB Type-C (M) to HDMI (M) cable |
| C-USBC/HM-10 | USB Type-C (M) to HDMI (M) cable |
| C-USBC/HM-15 | USB Type-C (M) to HDMI (M) cable |