



Galil 4-O

4-Inch, 2-Way On-Wall Speakers

| Speakers



The Galil 4-O On-wall Compact Speaker features a multi-tap power transformer for selecting 8 Ω (bypassing the transformer) or 70V/100V power settings that are suitable for an array installation. Available in white or black

FEATURES

Type - 2-way on-wall speaker

Woofer - 4" polypropylene cone

Tweeter - 0.5" Mylar dome

Impedance - 8 Ω

Power Handling - 20W RMS, 60W continuous program

Transformer Taps - 70V: 5W/2.5W/1.2W/Off (Lo-Z); 100V: 10W/5W/2.5W/Off (Lo-Z)

Package Includes - 2 speakers (1 pair)



TECHNICAL SPECIFICATIONS

DESCRIPTION:	2-way on-wall speakers
FREQUENCY RESPONSE:	90Hz to 20kHz @-10dB, 160Hz to 16kHz @±3dB
WOOFER:	4" (101.5mm) polypropylene cone
TWEETER:	0.5" (13mm) Mylar
IMPEDANCE:	8Ω (transformer tap in off position)
TRANSFORMER TAPS:	70V – 5W/2.5W/1.2W/Off (Lo-Z), 100V – 10W/5W/2.5W/Off (Lo-Z)
SENSITIVITY:	89dB 1W @1m
MAX SPL:	Continuous:95dB, peak: 98dB
POWER HANDLING:	20W RMS, 60W continuous program
CROSSOVER FREQUENCY:	6kHz
DIRECTIVITY FACTOR (Q):	4 averaged 1kHz to 10kHz
DIRECTIVITY INDEX (DI):	6dB averaged 1kHz to 10kHz
INPUT CONNECTORS:	Terminal blocks
MATERIALS:	Frame, grill and brackets steel; cabinet ABS
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F)
HUMIDITY:	10% to 90%, RHL non-condensing
WEIGHT PER SINGLE SPEAKER:	1.2kg (2.65lbs) approx
WEIGHT WITH MOUNTING KIT:	1.6kg (3.5lbs) approx
SHIPPING WEIGHT (FOR PAIR):	3.2kg (7.05lbs) approx
DIMENSIONS with mounting brackets:	18.5cm x 10.7cm x 20.9cm (7.28" x 4.23" x 8.2"), W, D, H
INSTALLATION CLEARANCE:	Front panel to wall (with mounting bracket): 15cm (5.9"), back panel to wall (with mounting bracket): 4.5cm (1.8")
ACCESSORIES:	2 mounting brackets (including 4 knobs and 4 mounting screws)
OPTIONS:	BCP-2S speaker cable
COLORS:	Available in white or black



CONFIGURATIONS

GALIL 4- O(PAIR)/BLACK	4-Inch, 2-Way On-Wall Speakers - Black
---------------------------	--

GALIL-4- O(PAIR)/WHITE	4-Inch, 2-Way On-Wall Speakers - White
---------------------------	--
