



K-180Mini

Panocam 4K@3 lens 180-degree FOV fixed focus; 2 Mic AI-powered auto framing, face detection, touch-button, multi-display modes



Smart panoramic camera that keeps everyone in view. Get the full picture even in the smallest meeting room. This 4K wall-mount camera captures clear video across a full 180° field of view, ensuring even people sitting close to the camera and on the far sides of the room are clearly seen. It automatically recognizes and zooms in on meeting participants, follows speakers as they move around, and auto-adjusts when attendee numbers change.

FEATURES

Immersive video conferencing experience -

Extreme wide-angle view, with three cameras providing a distortion-free 180° view that covers the whole room

Intelligent auto-framing and auto-tracking keep the presenter in focus

Easy and versatile operation -

Choice of 4 video layouts, with single-tap switching between them

Acts as a USB hub, enabling the K-Speak or any other speakerphone to be connected directly to the camera

Works with most common video conferencing platforms

Type-C Connection - Type-C connection enables seamless operation for a wide range of devices



TECHNICAL SPECIFICATIONS

Ports	1 USB 2.0 type A: On a USB connector 1 USB-C 2.0: On a USB-C connector
USB Features	Integrated USB Hubs 1
Video	Output Formats: MJPG; H.264; YUY2 Resolutions: YUY2 (30fps): 640x480, 640x360, 480x270, 352x288, 320x240 MJPG (30fps): 3840x2160(24fps), 3840x1376, 3840x962, 2560x1440, 1920x1080, 1280x720, 1024x576, 960x544, 640x480, 640x360 H264 (30fps): 1280x720, 1024x576, 960x544, 640x480, 640x360
Focus	Method: Fixed Distance: 1.5 meters
Camera	Max. Field of View (FOV): 180 Depth of Field (DOF): 0.5 to 5 meters Aperture: 2.2 Minimum Illumination: 10Lux
Microphone	Quantity: 2 Pickup Distance: Up to 4 meters
Controls	Top Button: Selectable layouts App: Layout configuration via PC
Power	Consumption: 5V/950mA 4.7W
Environmental Conditions	Operating Temperature: 0° to +40°C (32° to 104°F) Storage Temperature: -20° to +60°C (-4° to 140°F) Humidity: 10% to 90%, RHL non-condensing Altitude: Below 5000 meters
Regulatory Compliance (Standards Compliance)	Safety: CE, FCC Environmental: RoHS, WEEE
Enclosure	Type: Aluminum
General	Net Dimensions (W, D, H): 14.7cm x 7.4cm x 3.5cm (5.8" x 2.9" x 1.4") Shipping Dimensions (W, D, H): 17.6cm x 17.6cm x 4.6cm (6.9" x 6.9" x 1.8") Net Weight: 0.24kg (0.53lbs) approx Shipping Weight: 0.59kg (1.3lbs) approx
Accessories	Included: 1 USB-C cable, wall bracket, and screws set
Product Dimensions	14.70cm x 7.40cm x 3.50cm (5.79" x 2.91" x 1.38") W, D, H

Product Weight 0.2kg (0.5lbs) approx

Shipping Dimensions 17.60cm x 17.60cm x 4.60cm (6.93" x 6.93" x 1.81") W, D, H

Shipping Weight 0.6kg (1.3lbs) approx

