CHERRY AK-C7000 MEDICAL KEYBOARD COMPACT

Compact disinfectable Medical Keyboard with num pad



															1 A	1	
Esc	F1	F2	F3	F4	F5	F6	F7	F8	P0	F10	F11	F12 (Raten))	Pause	Pos 1	Ende	Einfg	Druc
。 ^	1	2 2	9 3 3	\$ 4	% 5	& 6	/ 7 {	(8 [) 9 1	= 0 }	? ß \	2	-	Num	÷	*	-
₩	Q	W	E e	R	Т	Z	U	1	0	Ρ	Ü	* +~	*	7 Pos 1	8 †	9 Bid†	
Ð	A	S	D	F	G	Н	J	К	L	Ö	Ă	+	-	4 ≁-	5	6 →	+
Û	> <	Y	×	С	V	в	Ν	Μ _μ	;		-	1 [Clean]	Entf	1 Ende	2 ↓	3 Bid ¥	Ent
Sing	En	Win	Až					Alt Gr		Strg	Bid†	1	Bid #	0 Einfg		, Eef	
											-	1				0.0	

Models may vary from the image shown

The AK-C7000 Medical Keyboard with its compact size is an excellent choice for anyone who values hygiene, user-friendliness and flexibility. The waterproof silicone cover enables thorough wipedisinfection and reliably prevents the ingress of liquids, dust and dirt. Like all CHERRY keyboards, the AK-C700 is particularly easy to type on. The light keystroke and short key travel enable effortless and precise typing, which increases efficiency at work.

FUNCTION AND PERFORMANCE

- ightarrow Compact size with number pad
- → Approved for clinical wipe disinfection according to VAH list (German Association of Applied Hygiene)
- → Durable silicone cover with abrasion resistant labelling
- → Maximum writing comfort thanks to scissor technology
- ightarrow Short key travel and solid tactile feedback
- → Clean function: keys are switched off during the cleaning process

TECHNICAL DATA

Weight main product:	730 g
Weight of product without packaging:	796 g
Dimensions product without packaging:	374 mm x 139 mm x 25 mm
Weight of product incl. packaging:	879 g
Dimensions product incl. packaging:	395 mm x 195 mm x 30 mm
Content of master carton (pieces):	20
Weight of master carton incl. content:	17,500 g
Dimensions master carton:	410 mm x 340 mm x 420 mm
Cable length:	180 cm
Storage temperature:	-20 °C - 60 °C
Working temperature:	0 °C - 50 °C
Product approvals:	 CE EU RoHS FCC EN60601-1-2-2015 (IEC 4th edition)
System Requirements- Hardware:	USB-A
Operating system:	All operating systems that support USB keyboard interface
Scope of delivery:	KeyboardManual
Reliability:	MTBF 90: > 10 Mio.
Switching characteristics:	tactile
Max. current consumption (mA) of keyboard:	25 mA
Actuating force (cN):	60 cN
Total Key Travel:	3 mm
Key labeling:	Silk screen printing on silicon membrane
Number of keys:	104
Special key functions:	FN KeyCleanFunction



Status LEDs:	in housing					
Key technology:	Scissor					
Keycap material:	ABS					
Protection class:	StandardIP 68					
Warranty:	2 years warranty					

Errors, technical changes and delivery options reserved. Technical information refers only to the specification of the products. Properties are not guaranteed.

SKU / EAN / UPC	Protection class	Color	Layout
AK-C7000F-UVS-W/NOR EAN 7061111015959 UPC	IP 68	white	PN (PanNordic)
AK-C7000F-U1-W/NOR EAN 7061111106930 UPC	Standard	white	PN (PanNordic)

Please contact your local CHERRY service and support teams or your CHERRY sales partners for versions available in your country.